



Pressure calibration made fast and easy

The Beamex® POC6 is an accurate and user-friendly automatic pressure output controller, providing regulated output from vacuum to 70 bar (1015 psi).

The POC6 communicates with the Beamex® MC5P Calibration Host Module and with the portable Beamex® MC5 Multifunction Calibrator, enabling fully automatic calibration of pressure transmitters and other pressure instruments.



The POC6 can be delivered as panel mounted to Beamex® MCS100 Workstation or as a portable desk top version.

The POC6 can be used as a stand-alone pressure controller or as integrated to the Beamex calibration system.

Together with the MC5 family and Beamex® CMX Calibration software, the POC6 offers a fully automated, integrated solution for performing, documenting and managing calibrations easily, efficiently and accurately.

Beamex® POC6 Automatic Pressure Controller



The Beamex® POC6 can be used as a stand-alone pressure controller or together with Beamex® MC5 and MC5P Calibrators.

Main features

Main features	
Communicates with Beamex® MC5P and MC5 Calibrators	Easy-to-use
-1 to 70 bar (different ranges)	Panel mounted or portable desk top version
Precision < 0.015 % FS	High-speed regulation

Applications

Applications

Calibration of process instruments, such as pressure transmitters, sensors, gauges, indicators, recorders

Suitable for workshops, laboratories and on site calibration

Especially industries and plants that have a large number of instruments and/or perform a lot of calibrations





POC6 — Main Features





1. User friendly

The POC6 is fast and efficient to use with its touch screen.

2. Panel mounted into Beamex® Workstation

The POC6 can be delivered and used as panel mounted into a Beamex® MCS100 Workstation.

3. Portable desk top version

The POC6 can also be used as a desk top pressure controller, which makes it a very mobile solution.

4. Part of Beamex® Integrated **Calibration Solution**

Together with the Beamex® MC5 or MC5P calibrators as well as the Beamex® CMX Calibration Software, the POC6 offers an integrated, automated calibration system for performing, documenting and managing calibrations easily and efficiently.







The POC6 can be panel mounted into Beamex® MCS100 Workstation, Mobile Trolley or Desktop Cabinet.

POC6 – General Specifications

General Specifications

Feature	Specification	
Display	7.0" color LCD with touch screen	
Weight	Approx. 9.1 kg (20 lbs)	
Dimensions	228(w) x 148(h) x 310(d) mm (without handle)	
Digital interface	RS232, Ethernet, IEEE-488,	
Power consumption	Max. 90 VA	
Warranty	2 years	
Supported user interface languages	English, German, French, Spanish, Italian, Chinese, Russian, Japanese, Polish, Portugese, Korean	
Communication emulation	DPI510	
Connections	Pressure supply, Vacuum supply, Test port All connections 7/16"-20 SAE	

Specifications

Feature	Specification
Output range	± 1 bar (±14.5 psi) -1 to 6 bar (-14.5 to 87 psi) -1 to 20 bar (-14.5 to 290 psi) -1 to 70 bar (0 to 1015 psi) Special range within -0.95 to 70 bar (-13.5 to 1015 psi)
Precision	< 0.015 % FS
1 year uncertainty	< 0.025 % FS
Pressure units	33 selectable and 2 programmable
Control stability	< 0.004 % FS
Slew rate	< 3 sec. (regarding a 10 % press. increase in a 250 ml test volume)
Control range maximum	From 0 up to 100 % FS
Test volume	50 to 1,000 ccm (without throttle)
Pressure media	Clean dry non-corrosive gases
Overpressure protection	Safety relief valve
Resolution	4 to 6 digits
Measuring rate	25/sec
Warm-up time	Approx. 15 min
Max overpressure	Supply high port 105 to 110 % FS Test port max. 105 % FS
Compensated temperature range	15 to 45°C
Operation temperature	050°C

Installation alternatives

- Portable unit
- Panel mounted into a workstation
- MCS100 Workstation
 MCS100 Desktop Cabinet
 MCS100 Mobile Trolley

Options

- Barometric reference module
- Enables the controller to be used in absolute pressure

Standard Accessories

- User guide
- Accredited calibration certificate
- Mains cable



RELATED PRODUCTS AND SERVICES

Portable Calibrators

Beamex's range of portable MC-calibrators for field calibration is known for their accuracy, versatility and also for meeting both high and uncompromised quality standards. CMX Professional has built-in communication with Beamex's documenting calibrators.

Workstations

A workstation can be considered ideal when most of the maintenance and calibration tasks are performed in the workshop. Beamex's workstation is a modular testing and calibration system designed for use in workshops and laboratories

Professional Services

An essential part of a complete calibration solution are our Professional Services – service and re-calibration, implementation and training, software support, validation services and integration services. Working with you step-by-step, from implementation to support and recalibration, Beamex's Professional Services help you to get the most from your calibration investment.

Calibration Software

The Beamex® CMX Calibration Software is calibration management software that assists in documenting, planning, analyzing and, finally, optimizing calibration work. CMX's scalable technology and user configuration allows you to integrate it easily into other systems for a one-of-kind calibration system that fits your specific needs completely.

CMX also helps to meet the regulatory requirements, whether your plant's calibration system needs to comply with ISO 17025, cGMP or 21 CFR Part 11. By using CMX, you will have all your calibration results in a traceable and auditable form, either printed on paper or stored in electronic format in a database.

www.beamex.com

Portable calibrators

Workstations

Calibration software

Professional services

Industry solutions